



FAC350

Conventional VAD, Shallow Base, Ceiling Mount - Red Flash

General

The FAC350 is a general purpose ceiling mount LED beacon for fire alarm applications. It features a special base containing all wiring connections and allow for easy removal/placement of the device. With an EN54-23 approved coverage pattern of C-3-8.9, each FAC350 may be mounted up to 3m high and provide a 8.9m cylinder diameter coverage. A room size of 6.3 x 6.3m square room may therefore be covered with a single device.

Easy and Fast Installation

The FAX350 beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these beacons use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a "twist and click" action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The FAX350 beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area. The flash rate of the beacon may be adjusted during installation, with a selection of 0.5Hz or 1Hz.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the beacon from the base.



Details

- Automatic synchronisation
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- Flash rate selectable

FAC350

Conventional VAD, Shallow Base, Ceiling Mount - Red Flash

Technical specifications

Elektrische Angaben

Operating voltage	17 to 60 VDC
-------------------	--------------

Physikalisch

Physical dimensions	100 x 81 mm (Ø x D)
---------------------	---------------------

Net weight	215 g
------------	-------

Colour	Red
--------	-----

Material	High impact polycarbonate
----------	---------------------------

Umweltbedingungen

Operating temperature	-25 to +70°C
-----------------------	--------------

Relative humidity	5 to 95% noncondensing
-------------------	------------------------

Environment	Indoor
-------------	--------

IP rating	IP21
-----------	------

Regulativ

Certification	EN54-23
---------------	---------

Betrieb

Continuous

Current consumption

20mA @ 0.5 Hz / 40mA @ 1 Hz

Flash rate

0.5Hz or 1Hz

Automatic synchronisation

Phased start

Line monitoring input

Polarised input

Flash colour

Red

EN54-23 rating


Light coverage	C-3-8.9
----------------	---------

Mounting position	Ceiling
-------------------	---------

Mounting height	up to 3 m
-----------------	-----------

Floor coverage	up to 8.9 m diameter
----------------	----------------------

EN54-23 Coverage: C-3-8.9



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 15 February 2024 - 9:57