


# Product data sheet

Specifications



## Controller, EasyLogic, MP-C, BACnet MS/TP, 28 universal input/ output, 8 relay outputs

SXWMPC36AM10001

### Main

|                                       |   |
|---------------------------------------|---|
| Device Application                    | HVAC  |
| Product Or Component Type             | Field Controller                            |
| Device Short Name                     | MP-C-36A-M                                  |
| Function Available                    | Programmable<br>Smart Sensor Input          |
| Topology                              | Daisy chain                                 |
| Model                                 | MP-C-36A-MA                                 |
| Color                                 | Black                                       |
| Range                                 | EasyLogic                                   |
| Network Frequency                     | 50 Hz<br>60 Hz                              |
| Width                                 | 9.21 in (234 mm)                            |
| Mounting Mode                         | DIN Rail Mount<br>Panel-mounted             |
| Product Certifications                | RCM<br>cUL Listed<br>UL Listed              |
| Maximum Power Consumption In W        | 6 W   |
| Power Consumption In Va               | 12 VA                                       |
| Ambient Air Temperature For Storage   | -40...158 °F (-40...70 °C)                  |
| Display Type                          | Without Display                             |
| Ip Degree Of Protection               | IP20  |
| Ambient Air Temperature For Operation | 32...122 °F (0...50 °C) at normal operation |
| Input/Output Type                     | 28 universal I/O                            |
| Input Voltage                         | 0...10 V DC for universal input             |
| Relative Humidity                     | 0...95 % RH, non-condensing                 |
| Memory Type                           | 8 kB FRAM<br>32 MB flash<br>128 MB RAM      |
| [Us] Rated Supply Voltage             | 24 V AC +/- 20 %<br>24...30 V DC            |
| Number Of Outputs                     | 8 form A relay output                       |
| Height                                | 4.33 in (110 mm)                            |
| Depth                                 | 2.52 in (64 mm)                             |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                  |   |
|------------------|---|
| Protection Type  | MOV suppression<br>Internal fuse                            |
| Output Voltage   | 0...10 V DC for form A relay output<br>for universal output |
| Range Of Product | EasyLogic   |
| Range            | EasyLogic   |

## Complementary

|                             |  |
|-----------------------------|--|
| Product Brand               | Schneider Electric   |
| Switching Frequency         | 25 Hz  |
| Backup Time                 | 7 days   |
| Flame Retardance            | UL94-V0  |
| Communication Port Protocol | BACnet MS/TP   |
| Processor Name              | ARM Cortex-A7 dual core  |
| Standards                   | UL 916<br>ICES-003<br>EN 61000-6-2<br>EN 50491-5-3<br>EN 60730-1<br>EN 60730-2-11<br>EN 50491-3<br>EN 61000-6-3<br>EN 50491-5-2<br>UL 2043 |
| Range Compatibility         | EasyLogic controller   |
| Power Consumption In Va     | 10 VA  |

## Ordering and shipping details

|                   |                        |
|-------------------|------------------------|
| Category          | 80230-IG SEBA TO SEUSA |
| Discount Schedule | BMS1                   |
| Gtin              | 3606482219380          |
| Returnability     | Yes                    |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type Of Package 1       | PCE                     |
| Number Of Units In Package 1 | 1                       |
| Package 1 Height             | 2.76 in (7 cm)          |
| Package 1 Width              | 4.88 in (12.4 cm)       |
| Package 1 Length             | 9.37 in (23.8 cm)       |
| Package 1 Weight             | 21.55 oz (611 g)        |
| Unit Type Of Package 2       | S03                     |
| Number Of Units In Package 2 | 11                      |
| Package 2 Height             | 11.81 in (30 cm)        |
| Package 2 Width              | 11.81 in (30 cm)        |
| Package 2 Length             | 15.75 in (40 cm)        |
| Package 2 Weight             | 19.23 lb(US) (8.721 kg) |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant with Exemptions

China RoHS Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)